

VIVREAU ViTap

A stylish dispenser for chilled, sparkling and hot water.




Benefits

- Attractive design; easy to use
- Various combinations of chilled, sparkling and hot water to suit every environment
- Only the tap is installed on the work surface; the cooler-carbonator and boiler are concealed in the base cabinet

Two heights

- ViTap (dispensing height: 240 mm)
- ViTap Plus (dispensing height: 340 mm)



Anti-scalding feature for hot water


Easy-to-clean removable nozzles

Stainless steel tap

Drip tray with direct connection to waste water system

Easy Access Panel

additional control device (can be optionally installed and flexibly positioned)



Choice of up to five different configuration options

Available in a chrome or matte black finish

Perfect water flow with zero splash

Ideal for e.g.

- Executive lounges
- Bars
- Kitchenettes
- Breakfast buffets
- Staff rooms
- Wellness and spa areas



VIVREAU ViTap

Technical data



Model	BRITA VIVREAU ViTap 301	BRITA VIVREAU ViTap 302	BRITA VIVREAU ViTap 303	BRITA VIVREAU ViTap 304	BRITA VIVREAU ViTap 305
Design / type	Tap System				
Finish	Chrome	Chrome	Chrome	Chrome or Matte black	Chrome or Matte Black
Types of water					
Chilled still	•	•	-	•	•
Sparkling	-	•	-	-	•
Hot	-	-	•	•	•
Specifications					
Cooling capacity	60 l/h				
Fits into base cabinet with the following dimensions (W x H x D)	300 x 800 x 600 mm	500 x 800 x 600 mm	300 x 800 x 600 mm	600 x 800 x 600 mm	600 x 800 x 600 mm
Unit dimensions under the sink (W x H x D)	210 x 440 x 360 mm (cooler)	360 x 440 x 360 mm (cooler-carbonator)	130 x 523 x 320 mm (boiler)	210 x 440 x 360 mm (cooler) 130 x 523 x 320 mm (boiler)	360 x 440 x 360 mm (cooler-carbonator) 130 x 523 x 320 mm (boiler)
Unit dimensions incl. drip tray (W x H x D)	ViTap standard: 138 x 325 x 165 mm ViTap Plus Upgrade Kit: 210 x 420 x 230 mm (order number: 1023678)				
Dispensing height	ViTap standard: 240 mm ViTap Plus Upgrade Kit: 340 mm (order number: 1023678)				
System weight	19 kg (cooler) 1.6 kg (tap)	39 kg (cooler-carbonator) 1.6 kg (tap)	7.5 kg (boiler) 1.6 kg (tap)	19 kg (cooler) 7.5 kg (boiler) 1.6 kg (tap)	39 kg (cooler-carbonator) 7.5 kg (boiler) 1.6 kg (tap)
Max. power consumption	240 W	520 W	2800 W	3040 W	3320 W
Max. flow rate	2 l/min				
Specifications: Hot water					
Dispensing capacity	-	-	3-4 cups per minute at up to 95 °C		
Boiler tank capacity	-	-	4.5 l		
Order number					

The food-grade quality and safety of BRITA water filter products are tested and verified by independent institutions



*applies to all materials that come into contact with water